

osaka

Osaka OC-24 24000 BTU



Descriere :

Caracteristici

- Ventilator cu palete 3D
- Pompa de condens incorporata

Funcții

- Dezumidificare
- Sleep
- Autorestart
- Functie anti jet de aer rece
- Functie de auto-dezghetare

Detalii tehnice :

Capacitate de racire (kW Btu/h)	7.3 24000
Capacitate de Incalzire (kW Btu/h)	7.62 26000
Sursa de alimentare	220~240 / 1 / 50
Putere racire	2475 W
Putere incalzire	2428 W
Curent nominal racire	12.5 A
Curent nominal incalzire	11.8 A
Debit de aer (Hi/Mi/Lo) m3/h	1327/1114/871
Interval de functionare °C	-7/+43
UNITATE INTERIOARA	
Nivel de zgomot (Hi) dB(A)	48/45/39

Dimensiune carcasa (L x H x A)	840x230x840 mm
Dimensiune ambalaj (L x H x A)	900x250x900 mm
Dimensiune panel (L x H x A)	950x55x953 mm
Dimensiune ambalaj panel (L x H x A)	1035x90x1035 mm
Greutate neta caseta (kg)	24
Greutate bruta caseta (kg)	30
Greutate neta panel (kg)	5
Greutate bruta panel (kg)	8
Teava condens mm	32
UNITATE EXTERIOARA	
Nivel de zgomot	55 dB(A)
Agent frigorific	R410A
Tevi de conexiune Gaz	15.9 mm
Tevi de conexiune Lichid	9.52 mm
Lungime maxima tevi m	25
Dimensiune carcasa (L x H x A)	845x695x335 mm
Dimensiune ambalaj (L x H x A)	965x755x395 mm
Greutate neta	51 kg
Greutate bruta	54.5 kg