

osaka

Osaka OC-48 48000 BTU



Descriere :

Caracteristici

- Ventilator cu palete 3D
- Pompa de condens incorporata

Funcții

- Dezumidificare
- Sleep
- Autorestart
- Functie anti jet de aer rece
- Functie de auto-dezghetare

Detalii tehnice :

Capacitate de racire (kW Btu/h)	14.06 48000
Capacitate de Incalzire (kW Btu/h)	14.94 51000
Sursa de alimentare	380 / 3 / 50
Putere racire	5515 W
Putere incalzire	5580 W
Curent nominal racire	9.27 A
Curent nominal incalzire	9.63 A
Debit de aer (Hi/Mi/Lo) m3/h	1545/1354/1187
Interval de functionare °C	-7/+43
UNITATE INTERIOARA	
Nivel de zgomot (Hi) dB(A)	51/47/43

Dimensiune carcasa (L x H x A)	840x300x840 mm
Dimensiune ambalaj (L x H x A)	900x320x900 mm
Dimensiune panel (L x H x A)	950x55x950 mm
Dimensiune ambalaj panel (L x H x A)	1035x90x1035 mm
Greutate neta caseta (kg)	28.6
Greutate bruta caseta (kg)	32.6
Greutate neta panel (kg)	5
Greutate bruta panel (kg)	8
Teava condens mm	32
UNITATE EXTERIOARA	
Nivel de zgomot	63 dB(A)
Agent frigorific	R410A
Tevi de conexiune Gaz	19 mm
Tevi de conexiune Lichid	9.52 mm
Lungime maxima tevi m	50
Dimensiune carcasa (L x H x A)	900x1167x340 mm
Dimensiune ambalaj (L x H x A)	1032x1307x443 mm
Greutate neta	94 kg
Greutate bruta	106 kg